



3121 Fuel Hose



DESCRIPTION

Flexible, green hose for leaded or unleaded petrol. Good weather and ozone resistance and good resistance to oil spray in engine compartments of cars.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	3121
Application	Diesel, Fuel hose
Standard length	50 metres
Working temp.	-35°C to 135°C
Inside compound	NBR/PVC
Inside colour	Black
Outside compound	CSM
Outside colour	Green
Reinforcement	Polyester
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
4,0	10,8	5	30	33	118	3121040000
4,8	11,6	5	30	35	129	3121048000
5,6	12,4	5	30	37	140	3121056000
6,3	13,1	5	30	40	150	3121063000
7,6	14,4	5	30	43	170	3121076000
9,5	16,3	5	30	49	198	3121095000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

[End of life evaluation for production of Rubber hoses with Textile reinforcement](#)

16-05-2026