



1705 Material Handling Hose



DESCRIPTION

Hardwall hose used for suction and delivery of dry cement, sand, gravel, etc. Also available in other lengths, dimensions etc.

Please contact CODAN for further information.

ADDITIONAL INFORMATION

Type no.	1705
Application	Dry cement
Standard length	15 metres
Working temp.	-30°C to 70°C
Inside compound	SBR/NR
Inside colour	Black
Outside compound	EPDM
Outside colour	Black
Reinforcement	High Tensile Strength Synthetic Cord. Helix wire and ant
Standards	DIN 53516: 70 +/-5mm3
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
114,0	138,0	10	30	â€“	6340	1705114000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

24-03-2025