



# 1005 Air - Water Hose



## DESCRIPTION

Black, reinforced, layflat water hose. Easy to handle and extremely space-saving. Flexible, even when used at low temperatures.

Often used on building sites for immersion pumps, etc. or where liquids are carried under pressure.

Normally installed using hose clamps, Bauer or Stortz fittings, or similar.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	1005
Application	Air - water hose
Standard length	40 metres
Working temp.	-30°C to 90°C
Inside compound	EPDM
Inside colour	Black
Outside compound	EPDM
Outside colour	Black
Reinforcement	Polyester
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
25,0	31,4	5	15	250	420	1005025000
32,0	38,4	5	15	300	520	1005032000
38,0	44,4	5	15	380	610	1005038000
45,0	51,4	5	15	440	700	1005045000
51,0	57,4	5	15	500	790	1005051000
63,0	70,0	5	15	630	960	1005063000
76,0	82,4	5	15	750	1450	1005076000
102,0	110,0	5	15	1000	1580	1005102000
110,0	117,2	5	15	1120	1730	1005110000
127,0	134,2	5	15	1250	2000	1005127000
152,0	165,2	5	15	1500	2380	1005152000
203,0	211,4	5	15	2000	3750	1005203000
254,0	264,0	5	15	2500	5680	1005254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64  
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

[End of life evaluation for production of Rubber hoses with Textile reinforcement](#)

15-04-2026