



# 5034 Air Conditioning



## DESCRIPTION

Black, flexible high-quality hose with exceptional inner liner of CIIR rubber which prevents Freon R134a from permeating the hose.

For use in mobile and stationary refrigeration systems in which R134a is used.

Purpose-approved, crimped-on fittings are recommended.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	5034
Application	Air conditioning hose
Standard length	50 metres
Working temp.	-30°C to 120°C
Inside compound	CIIR
Inside colour	Black
Outside compound	EPDM
Outside colour	Black
Reinforcement	PVA
Standards	SAE J2064:2011, Type A & SAE J 3062: 2015
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
8,0	18,4	24	137	70	325	5034008000
10,5	22,4	24	137	90	440	5034010000
13,0	24,8	24	137	100	515	5034013000
16,0	27,8	24	137	110	600	5034016000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64  
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

17-04-2025