



# 1918 Oil Hose



## DESCRIPTION

Black, wrapped delivery hose with integrated anti-static wire and excellent low-temperature tolerance. Hard-wearing, weather-resistant outer layer of rubber. Inner rubber layer is resistant to max. 40% aromatics. For use as pressure oil hose and tanker hose in industrial applications.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	1918
Application	Oil/Fuel
Standard length	-
Working temp.	-35°C to 70°C
Inside compound	NBR
Inside colour	Black
Outside compound	CR
Outside colour	Black
Reinforcement	Polyester - Anti-static wire
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
19,0	31,0	18	54	â€“	630	1918019000
25,0	37,0	18	54	â€“	750	1918025000
32,0	44,0	18	54	â€“	950	1918032000
38,0	51,0	18	54	â€“	1200	1918038000
45,0	59,0	18	54	â€“	1550	1918045000
51,0	65,0	18	54	â€“	1700	1918051000
63,5	79,0	18	54	â€“	2400	1918063000
76,0	91,0	18	54	â€“	2650	1918076000
102,0	118,0	18	54	â€“	3700	1918102000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64  
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

17-04-2025