



# 2106 Oil Hose



## DESCRIPTION

Black, corrugated, lightweight, high-quality hose approved for use as wet diesel exhaust pipe and fuel pipe on boats less than 15 m in length. Max. 55% aromatics. Incorporated double steel helix allows the hose to be bent without kinking in small engine compartments with limited access. Fire retardant outer rubber coating. Normally installed using heavy-duty hose clamps tightened with Allen key.

Please contact Codan for further information.

## ADDITIONAL INFORMATION

Type no.	2106
Application	Marine Exhaust
Standard length	40 metres
Working temp.	-30°C to 100°C
Inside compound	NBR
Inside colour	Blue
Outside compound	CR
Outside colour	Black
Reinforcement	Polyester w/ double steel helix
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
25,0	34,0	10	30	100	670	2106025000
32,0	41,0	10	30	130	810	210632000
38,0	47,0	10	30	150	940	2106038000
40,0	49,0	10	30	165	990	2106040000
42,0	51,0	10	30	170	1040	2106042000
45,0	54,0	10	30	180	1110	2106045000
48,0	57,0	10	30	190	1411	2106048000
51,0	60,0	10	30	200	1500	2106051000
55,0	65,0	8	24	220	1765	2106055000
60,0	70,0	8	24	240	1923	2106060000
63,0	73,0	8	24	250	2020	2106063000
70,0	80,0	7	21	280	2201	2106070000
76,0	86,0	7	21	300	2390	2106076000
80,0	90,0	7	21	320	2515	210608000
90,0	100,4	7	21	360	2830	210609000
102,0	113,0	7	21	450	3320	2106102000
152,0	164,0	6	18	700	6980	2006152000
203,0	217,0	5	15	950	9710	2106203000
254,0	270,0	5	15	1250	13777	2106254000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
305,0	322,0	5	15	1500	15410	2106305000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64  
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

17-04-2025