



2052 PVC Hose



CODAN 2052 UNIVERSAL LAY FLAT EXTRACTION HOSE

DESCRIPTION

Flat hose reinforced with polyester yarn, medium pressure. Mainly for conveying water.

ADDITIONAL INFORMATION

Type no.	2052
Application	Layflat, PVC hose
Standard length	-
Working temp.	-20°C to 50°C
Inside compound	PVC
Inside colour	Black
Outside compound	PVC
Outside colour	Blue
Reinforcement	Polyester
Standards	-
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
25,0	29,0	7	15	∞	∞	2052025000
32,0	36,0	7	15	∞	200	2052032000
38,0	41,0	5	15	∞	230	2052038000
50,0	54,0	∞	15	∞	333	2052050000
63,0	69,0	4	15	∞	430	2052063000
76,0	82,0	4	10	∞	570	2052076000
102,0	108,0	4	10	∞	865	2052102000
125,0	133,0	3	10	∞	1080	2052125000
152,0	160,0	3	10	∞	1482	2052152000
200,0	211,0	3	8	∞	2020	2052200000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

[End of life evaluation for production of Rubber hoses with Textile reinforcement](#)