



2152 PVC Hose



DESCRIPTION

Red, cadmium-free, reinforced PVC hose for air, water, certain chemicals. Wine, fruitjuice, lemonade and mineralwater under pressure. Polyester fabric liner provides stable working and bursting pressures and great flexibility. Transparent design allows effective flow control. Tolerances acc. to DIN 16940. Normally installed using hose clamps.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	2152
Application	Universal, PVC
Standard length	50 metres
Working temp.	-20°C to 65°C
Inside compound	PVC
Inside colour	Transparent
Outside compound	PVC
Outside colour	Red
Reinforcement	Polyester
Standards	2002/72/EC, CL. ABC
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
10,0	16,0	10	40	40	â€“	2152010000
13,0	19,0	10	40	70	â€“	2152013000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

24-03-2025