



1158 Steam Hose



DESCRIPTION

Red, heavy-duty, braided steam hose manufactured to ISO 6134:2017 Type 2A.

For use in industry for saturated steam and hot water in laundries, dairies, slaughterhouses, power stations, etc. Also available in black.

For steam, must be installed using special connectors. Crimped-on fittings are recommended for pressurised steam.

Please contact Codan for further information.

ADDITIONAL INFORMATION

Type no.	1158
Application	Saturated Steam and Water
Standard length	20/40 metres
Working temp.	-20°C to 203°C
Inside compound	EPDM
Inside colour	Black
Outside compound	EPDM
Outside colour	Red
Reinforcement	Stainless steel braided
Standards	ISO 6134:2017 Type 2A
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
13,0	25,0	17	170	70	550	1158013000
16,0	30,0	17	170	85	655	1158016000
19,0	33,0	17	170	100	770	1158019000
25,0	40,0	17	170	140	1030	1158025000
32,0	47,0	17	170	200	1270	1158032000
38,0	53,0	17	170	250	1470	1158038000
44,0	61,0	17	170	288	1945	1158044000
51,0	68,0	17	170	350	2500	1158051000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark Tel. +45 56 64 64 64
Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

[End of life evaluation for production of Rubber hoses with Textile reinforcement](#)

08-03-2026